

JXSC Mine Machinery Factory Compound Cone Crusher Specification

Model	Cavity Type	Stroke (mm)	Max.Feeding Size (mm)	Discharging Opening Adjusted Scope(mm)	Capacity(t/h)	Motor Power(kw)	Weight(t)
DN1650C2-D	Coarse	34	300	35-65	280-610	250	35
DN1650C-D	Coarse	34	260	30-60	2665-580	250	35
DN1650Z-D	Medium Coarse	34	240	25-60	240-550	250	35
DN1650S-X	Fine	28	130	20-45	180-350	250	35
DN1400C-D	Coarse	30	235	30-60	210-530	220	25
DN1400Z-D	Medium Coarse	30	215	25-50	200-500	220	25
DN1400Z-X	Medium Coarse	25	180	22-45	180-475	220	25
DN1400S-X	Fine	25	100	19-40	130-260	220	25
DN1200C-D	Coarse	22	180	19-50	110-250	132	16
DN1200S-X	fine	15	80	16-40	80-180	132	16
DN1000C-D	Coarse	20	160	16-35	70-215	110	14
DN1000Z-D	Medium Coarse	18	115	16-30	55-135	110	14
DN1000S-X	fine	15	80	10-25	47-90	110	14

Address: The Industrial park,
Shicheng country, Ganzhou city,
Jiangxi province, China
Mobile Phone/Whatsup:
+86-13879771862
Email:sales@jxscmine.com

